

Cerbo API:

Partner Application Endpoints:

Please note: All dates listed (creation times, sign dates, date of service, update-times) are listed in UTC, so you'll want to adjust for **your local timezone**.

1. **Get all electronically-submitted orders to Quest Diagnostics for a patient**

Endpoint: /v1/patients/:patient_id/partners/quest/orders

Method: GET

Arguments:

- limit: (optional) defaults to 100, but can be overridden (max is 100)
- offset: (optional) If the returned data indicates that there are more responses than the limit (has_more: true), then it will offset the list to allow you to cycle through further results

Sample Call:

```
curl -X GET https://un:pwd@subdomain.md-hq.com/api/v1/patients/1/partners/quest/orders
```

2. **Get a single electronically-submitted order to Quest Diagnostics by the Quest order ID**

Endpoint: /v1/partners/quest/orders/:order_id

Method: GET

Arguments:

- None

Sample Call:

```
curl -X GET https://un:pwd@subdomain.md-hq.com/api/v1/partners/quest/orders/2
```

Sample Response:

```
{"object": "quest_order", "id": "2", "pt_id": "1", "status": "1", "addedby": "71", "dateadded": "2018-11-30 15:45:54", "deletedby": "0", "datedeleted": null, "name": "Quest Order: 11-30-2018", "pt_orders": [{"id": "5", "url_pt_order_details": "https://subdomain.md-hq.com/api/v1/patients/1/orders/5"}, {"requisition_documents": [{"id": "3", "url_quest_requisition_content": "https://subdomain.md-hq.com/api/v1/partners/quest/requisitions/3/content"}]}
```

3. **Get the raw requisition document for an electronically-submitted order to Quest Diagnostics by the requisition ID**

Endpoint: /v1/partners/quest/requisition/:order_id/content

Method: GET

Arguments:

- None

Sample Call:

```
curl -X GET https://un:pwd@subdomain.md-hq.com/api/v1/partners/quest/requisition/3/content
```