

Cerbo API:

## Appointment Endpoints:

Please note: All dates listed (start times, end times, creation times) are listed in UTC, so you'll want to adjust for your local timezone. Also, associated providers returns an array of provider objects, as a single appointment can be assigned to multiple providers or resources.

### 1. Get All Appointments in a Date Range

*Endpoint:* /api/v1/appointments

*Method:* GET

*Arguments:*

- limit: (optional) defaults to 1000, but can be overridden (max is 1000)
- offset: (optional) If the returned data indicates that there is more than the limit responses (`has_more: true`), then it will offset the list to allow you to cycle through long appointment list
- start\_date: (required) Y-m-d string for first day of date-range
- end\_date: (require) Y-m-d string for last day of date-range
- provider\_id: (optional) integer for the ID of a specific provider limits results to specific user appointments
- pt\_id: (optional) integer for the ID of a specific patient to get appointments for.
- include\_cancelled: (optional) if not empty, it will include cancelled appointments in the return (these are suppressed by default)
- include\_work\_schedule: (optional) include details about when a provider is set to work (these are suppressed by default)
- status: (optional) a string or an array to filter only appointments of specific statuses – these include: scheduled, confirmed, checked-in, in-room, cancelled, and possibly custom statuses set by your clinic.

*Sample Call:*

```
curl -X GET https://un:pwd@subdomain.md-hq.com/api/v1/appointments?
limit=10&start_date=2017-01-01&end_date=2017-12-31&provider_id=7&status\
[\]=confirmed&status\[]=scheduled
```

### 2. Get a single appointment's details

*Endpoint:* /api/v1/appointments/:appointment\_id

*Method:* GET

*Arguments:* [none]

*Sample Call:*

```
curl -X GET https://un:pwd@subdomain.md-hq.com/api/v1/appointments/214
```

### 3. Insert a new appointment

*Endpoint:* /api/v1/appointments

*Method:* POST

*Arguments:*

- start\_date\_time: (required) Y-m-d H:i timestamp for the visit start date/time
- end\_date\_time: (required) Y-m-d H:i timestamp for the visit end date/time

- **provider\_ids**: (required) integer or array of integers for which providers and resources the appointment is for
- **pt\_id**: (optional) integer for the ID of a specific patient to get appointments for.
- **appointment\_type** (required) Valid Appointment Type ID
- **title** (required) The display title of the appointment
- **appointment\_note** (required) String for accompanying note for the appointment
- **status**: (optional) a string or an array to filter only appointments of specific statuses – these include: scheduled, confirmed, checked-in, in-room, cancelled, and possibly custom statuses set by your clinic. Defaults to “scheduled”
- **telemedicine**: (optional) boolean for whether this should be scheduled as a Telemedicine visit (with an attached video URL), defaults to false

*Sample Call:*

```
curl --data '{"start_date_time":"2018-08-11 14:30","end_date_time":"2018-08-11 15:00","provider_ids":[8,14],"pt_id":2,"title":"Initial Visit","appointment_note":"John has been having headaches","appointment_type":"Office Visit"}' -X POST https://un:pwd@subdomain.md-hq.com/api/v1/appointments
```

#### 4. Update existing appointment

*Endpoint:* /api/v1/appointments/:appointment\_id

*Method:* PATCH

*Arguments:*

- Same as adding a new appointment, EXCEPT telemedicine is not supported at this time

*Sample Call:*

```
curl --data '{"start_date_time":"2018-08-11 15:30","end_date_time":"2018-08-11 16:00","appointment_note":"Needs to move appointment back by a couple of hours"}' -X PATCH https://un:pwd@subdomain.md-hq.com/api/v1/appointments/524563
```

#### 5. Delete/Remove existing appointment

*Endpoint:* /api/v1/appointments/:appointment\_id

*Method:* DELETE

*Arguments:* [none]

*Notes:* This method should be used to completely remove an appointment. If you are looking to Cancel an appointment please use the update endpoint and set the `status` to “cancelled”

*Sample Call:*

```
curl -X DELETE https://un:pwd@subdomain.md-hq.com/api/v1/appointments/542
```

#### 6. Get all appointment types

*Endpoint:* /api/v1/appointment\_types

*Method:* GET

*Arguments:*

- **limit**: (optional) defaults to 1000, but can be overridden (max is 1000)

- offset: (optional) If the returned data indicates that there is more than the limit responses (`has_more: true`), then it will offset the list to allow you to cycle through long appointment list
- include\_deleted: (optional) if not empty, it will include appointment types which have been deleted/removed.

*Sample Call:*

```
curl -X GET https://un:pwd@subdomain.md-hq.com/api/v1/appointment_types
```

*Notes:* If the `email_reminder_hrs_before` or `sms_reminder_hrs_before` values are less than zero, it means that they inherit the timing from the default practice settings